



# SMILE-G3



Model	SMILE-G3-S3.6	SMILE-G3-S5	SMILE-G3-B5
<b>System Specification</b>			
Nominal Output Power	3680 W	5000 W	5000 W
Capacity Range	10.1 ~ 60.5 kWh (95% DoD)		
Battery Chemistry	LFP (LiFePO4)		
IP Protection	IP65 (Outdoor)		
System Dimension (W x D x H)	610 x 230 x 1168 mm (with Bracket)		
System Weight	109.5 kg		
Warranty	5 Year Product Warranty, 10 Year Battery Performance Warranty		
<b>Inverter Technical Specification</b>			
Model	SMILE-G3-S3.6-INV	SMILE-G3-S5-INV	SMILE-G3-B5-INV
Coupling	Hybrid	Hybrid	AC
Max. PV Input Power	7360 W	10000 W	NA
Max. PV Input Current	15 A / 15 A		NA
Max. PV Input Voltage	580 V		NA
MPPT Number/Max. Input Strings Number Per MPPT	2/1		NA
MPPT Voltage Range	100 ~ 550 V		NA
Max. PV Short-circuit Current	18.75 A / 18.75 A		NA
Max. Charging/Discharging Current	60 A		
Max. Charging/Discharging Power	3680 W	5000 W	5000 W
Rated Frequency	50 / 60 Hz		
Rated Voltage	230 V		
Rated Output Apparent Power (Grid Port)	3680 VA	5000 VA	5000 VA
Rated Output Apparent Power (Backup Port)	3680 VA	5000 VA	5000 VA
Max. AC input Power (Grid Port)	7360 W	10000 W	10000 W
Rated Output Current (Grid Port)	16 A	21.7 A	21.7 A
Max. AC Output Current (Grid Port)	16 A	21.7 A	21.7 A
Rated Output Current (Backup Port)	16 A	21.7 A	21.7 A
Max. AC Output Current (Backup Port)	16 A	21.7 A	21.7 A
Max Inverter Efficiency	97.3%		
Backup	UPS		
Communication	Ethernet / WiFi		
Humidity	0~90% (No Condensing)		
Dimension (W x D x H)	610 x 212 x 366 mm		
Weight	19.5 kg		
Safety	IEC 62109, IEC 62040		
EMC	EN61000-6-1/-2 /-3/-4		
Grid Regulation	AS4777.2, NRS 097		
<b>Battery Technical Specification</b>			
Module Mode	SMILE-G3-BAT-10.1P		
Module Capacity	10.1 kWh		
Usable Capacity	9.6 kWh		
Depth of Discharge (DoD)	95%		
Nominal Voltage	96 V		
Battery Voltage Range	91.5 V ~ 106.5 V		
Max. Charging/Discharging Current	52.5 A		
Operating Temperature Range	-10 °C ~ 50 °C*		
Cycle Life	8000**		
Battery Modules Connection	1 ~ 6 in Parallel		

\* When the ambient temperature is too low or too high, the performance of battery may be limited.  
 \*\* Under specific test conditions.



#### Alpha ESS Co., Ltd.

+86 513 8060 6891  
 info@alpha-ess.com  
 www.alphaess.com  
 Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

#### Alpha ESS Suzhou Co., Ltd.

+86 512 6828 7609  
 info@alpha-ess.com  
 www.alphaess.com  
 Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou 215000

#### Alpha ESS Europe GmbH

+49 610 3459 1601  
 europe@alpha-ess.de  
 www.alphaess.de  
 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

#### Alpha ESS Australia Pty. Ltd.

+61 402 500 520  
 Australia@alpha-ess.com  
 www.alphaess.com  
 Adelaide: 19 Heath St, Lonsdale SA5160  
 Sydney: 8/15-21 Gibbes Street, Chatswood, NSW 2067

#### Alpha ESS Italy S.r.l.

+39 339 462 4288  
 info@alpha-ess.it  
 www.alphaess.com  
 Via Don Minzoni, 17, Calenzano Firenze 50041

#### Alpha ESS UK Ltd.

+44 145 354 5222  
 info@alpha-ess.com  
 Drake House, Long Street, Dursley, gl11 4hh

#### Alpha ESS International Pte. Ltd.

+65 6513 1125 / +65 6513 1126  
 Singapore@alpha-ess.com  
 2 Corporation Road #01-06A Corporation Place Singapore 618494

#### Alpha ESS USA, Inc.

+1 408 368 7828  
 usa@alpha-ess.com  
 Unit 5, 2180 S Ivanhoe St, Denver, CO 80222

#### Alpha ESS Korea Co., Ltd.

info@alpha-ess.com  
 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea